

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 June 2001 (14.06.2001)

PCT

(10) International Publication Number
WO 01/42674 A1

(51) International Patent Classification⁷: **F16D 25/10**

Sverker [SE/SE]; Mastgatan 7, S-426 53 Västra Frölunda (SE).

(21) International Application Number: PCT/SE00/02482

(22) International Filing Date:
11 December 2000 (11.12.2000)

(74) Agents: HELLBOM, Lars et al.; Albihns Stockholm AB, P.O. Box 5581, S-114 85 Stockholm (SE).

(25) Filing Language: Swedish

(81) Designated States (*national*): BR, JP, US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(30) Priority Data:
9904550-2 13 December 1999 (13.12.1999) SE

(71) Applicant (*for all designated States except US*): VOLVO
LASTVAGNAR AB [SE/SE]; S-405 08 Göteborg (SE).


Published:
— With international search report.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): ALFREDSSON,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HYDRAULICALLY OPERATED DOUBLE CLUTCH



(57) Abstract: Hydraulically operated double clutch with first and second piston-cylinder devices for engagement and disengagement of the respective clutch unit. The cylinder chamber (17) of the first piston-cylinder device is delimited between its piston (18) and a first wall (4) of the clutch housing (1), while the cylinder chamber (24) of the second piston-cylinder device is delimited between its piston (25) and the first mentioned piston (18). A third cylinder chamber (30) is delimited between the piston (25) of the second piston-cylinder device and a second wall (6) of the clutch housing (1). Channels (31-34) are arranged for supply of pressure medium to and from the cylinder chambers, so that the pressure of the pressure medium in the engagement direction on either piston generates at the same time a return force on the other piston, balancing the force in the engagement direction generated by the centrifugal force on the pressure medium.

WO 01/42674 A1